



CERTIFICATE OF ACCREDITATION

The ANSI National Accreditation Board

Hereby attests that

Hexagon Manufacturing Intelligence, Inc.

46444 Hexagon Way
Novi, MI 48377

(and the satellite as listed on the scope)

Fulfills the requirements of

ISO/IEC 17025:2017

and the national standard

ANSI/NCSL Z540-1-1994 (R2002)

In the field of

CALIBRATION

This certificate is valid only when accompanied by a current scope of accreditation document.
The current scope of accreditation can be verified at www.anab.org.

R. Douglas Leonard Jr., VP, PILR SBU

Expiry Date: 14 December 2024

Certificate Number: AC-1745



This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory
quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

**SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017 AND
ANSI/NCSL Z540-1-1994 (R2002)**

Hexagon Manufacturing Intelligence, Inc.

46444 Hexagon Way
Novi, MI 48377
Sarah White
248-449-9443

CALIBRATION

Valid to: **December 14, 2024**

Certificate Number: **AC-1745**

Length – Dimensional Metrology

Parameter / Equipment ¹	Range	Expanded Uncertainty of Measurement (+/-) ²	Reference Standard, Method and/or Equipment
Length Bar Standard	Up to 1.2 m	$(2.8 + 0.47L) \mu\text{m}$	CMM
Articulated Arm CMM (AACMM) – Volumetric Performance	Up to 1.2 m	$(4 + 0.67L) \mu\text{m}$	ASME B89.4.22 Sections 5.3 and 5.4 Length Bar Standard
Articulated Arm CMM (AACMM) – Volumetric Performance	Up to 1.2 m	$(2.6 + 0.63L) \mu\text{m}$	ISO 10360-2 Sections 6.3 and 6.4 (adapted) Step Gage

Length – Dimensional Metrology

Parameter / Equipment ¹	Range	Expanded Uncertainty of Measurement (+/-) ²	Reference Standard, Method and/or Equipment
Articulated Arm CMM (AACMM) – Probing Size Error (P Size) ² Probing Form Error (P Form) ² Articulated Location Error (LDia) ² Length Measurement Error Unidirectional (EUni)	Sphere Diameter: Up to 51 mm Up to 51 mm Up to 51 mm Length: Up to 3 m	0.22 μm 0.13 μm 0.16 μm (2 + 2L) μm	ISO 10360-12 Test Sphere Test Sphere Test Sphere Scale Bar with conical seat
Articulated Arm Coordinate Measuring Machines (AACMM) with Optical Distance Sensors: Articulated Location Value (LDia) ²	Sphere Diameter: 51 mm	0.25 μm	ISO 10360-8 Annex D Test Sphere
Test Sphere Diameter ² Form ²	25.4 mm 50.0 mm 25.4 mm 50.0 mm	1.6 μm 4.4 μm 1 μm 1 μm	CMM
Length (Tracker with or without T-scan or T-probe)	(125 to 2 550) mm	14.1 μm	Scale Bar (Brunson kit, modular)
Length (Theodolites - Industrial Measurement Systems)	(125 to 2 550) mm	14.1 μm	Scale Bar (Brunson kit, modular)

Services performed at satellite location

9004 Research Drive
Irvine, CA 92618
Sarah White 248-449-9443

CALIBRATION

Length – Dimensional Metrology

Parameter / Equipment ¹	Range	Expanded Uncertainty of Measurement (+/-)	Reference Standard, Method and/or Equipment
Length (Tracker with or without T-scan or T-probe)	(125 to 2 550) mm	14.1 μ m	Scale Bar (Brunson kit, modular)
Length (Theodolites - Industrial Measurement Systems)	(125 to 2 550) mm	14.1 μ m	Scale Bar (Brunson kit, modular)

Calibration and Measurement Capability (CMC) is expressed in terms of the measurement parameter, measurement range, expanded uncertainty of measurement and reference standard, method, and/or equipment. The expanded uncertainty of measurement is expressed as the standard uncertainty of the measurement multiplied by a coverage factor of 2 ($k=2$), corresponding to a confidence level of approximately 95%.

Notes:

1. On-site calibration service is available for this parameter, since on-site conditions are typically more variable than those in the laboratory, larger measurement uncertainties are expected on-site than what is reported on the accredited scope.
2. L = Length in meter.
3. Dimensions are nominal value
4. This scope is formatted as part of a single document including Certificate of Accreditation No. AC-1745.



R. Douglas Leonard Jr., VP, PILR SBU